




00699 - HYDROCLEANER



Ready for use



Use clean industrial paper/cloth and wipe

DESCRIPTION

Water-borne, anti-silicone, antistatic and anti-dusting detergent cleaner.

USE

It removes surface light contamination, including silicone, with antistatic effect. Suitable for cleaning pre-existent coatings substrates. It degreases small bare metal surfaces. For cleaning larger areas 00695 SILICONE REMOVER SLOW is recommended.

Use prior to applying water-borne finishes.

CHARACTERISTICS

- Water-borne product.
- Excellent cleaning power.
- Good antistatic qualities
- Safe to use also on 1K nitro and synthetic coatings.
- Fast flash-off (do not use at high temperature).
- Removes tree sap residue.
- When stronger cleaning power is required use 00695 SILICONE REMOVER SLOW.

SUBSTRATE PREPARATION

Pre-clean the surface before painting.

APPLICATION:

Apply with clean clothes or industrial paper as follows:

- Wipe off the surface with cloth or paper wet with detergent
- Dry the surface with clean dry cloth or paper before product evaporates.
-

DIR 2004/42/CE: Preparatory and cleaning IIB/a – VOC ready for use 200 g/l
Maximum V.O.C. content 160 g/l VOC

RECOMMENDED OVERCOATINGS

Any product within the Lechler Car Refinish range can be used.

TECHNICAL DATA SHEET N° 0548-GB
UPDATED 01/2008

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.