

# Technical Datasheet

## Q 20-200 2K Polyester Fine Putty

### Characteristics:

2K Polyester Fine Putty is a very fine finishing polyester putty, designed for steel, aluminum and polyester laminates. It adheres also to zinc-coated surfaces up to 55°C. This putty is very smooth and easy to apply. It creates a perfect coating without pores. It dries fast and doesn't clog sandpaper.

### Application:

The surface must be clean, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener BPO by weight. Apply within 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

### Note:

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.

### Technical data:

Density: 1,75 g/cm<sup>3</sup>


Colour: blue




2004/42/II(b)(250)<250




Cleaning  
60-010



BPO- 2-3%



Pot life  
3 -5 min 20°C




16 - 30 min 20°C




Hand sanding / dry:  
P120 - P320



Machine sanding / dry:  
P120 - P320



Shelf life:  
12 Month



Store in cool place



Latex / Nitril

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017